

# PRODUCT INFORMATION



## RUST RAIDER

CODE: B532, B534,  
B540

PAGE: 1 of 1

DATE: 01/21/2008

**FUNCTION & APPLICATION:** A liquid boiler and heating system conditioner that prevents rust and corrosion in all steam and hot water heating systems. Added to new or clean systems, RUST RAIDER's special ingredients are carried to all parts of the system and return with the condensate to be recycled.

**OUTSTANDING PROPERTIES:** RUST RAIDER contains no poison. It is guaranteed completely harmless to metal. It contains an ingredient that shows whether it is strong enough in concentration in the system to effectively protect it from rust. RUST RAIDER turns the water blue. This simple method insures continuing protection for the boiler.

**USE DIRECTIONS:** Start with a system that is as clean as possible. **For old and new systems:** Use RUST RAIDER in proportion of 1 quart per 25 gallons of water, or 1 quart for every 375 square foot of standing radiation, or 90,000 Btu boiler capacity. Pour RUST RAIDER into system at any point, preferably in an upper boiler opening. **For new hot water systems:** Use in proportion of 1 quart per 25 gallons of water, or 2 quarts for each 375 square foot of standing radiation, or 67,000 Btu boiler capacity. **For old hot water systems:** Draw off 3 or 4 pails of water or enough to relieve highest point of system. Disconnect union elbow or valve from highest radiator. Use in proportion of 1 quart per 25 gallons of water, or 2 quarts for every 375 square foot of standing radiation, or 67,500 Btu boiler capacity. Fill system with water.

**PRECAUTIONS:** Contains Sodium Tetraborate decahydrate (CAS# 1303-96-4) and a proprietary blend of corrosion inhibitors. May be harmful if swallowed. Eye and skin irritant. **FIRST AID:** If swallowed, DO NOT INDUCE VOMITING! Call Poison Control Center, Physician, or Hospital Emergency Room immediately. For eye contact, flush thoroughly with water for 15 minutes while lifting eyelids and get prompt medical attention. For skin contact, wash thoroughly with soap and water. If irritation develops, get prompt medical attention. For Inhalation, move to fresh air. If breathing becomes difficult, get prompt medical attention.

**STORAGE & HANDLING:** Store in a cool place below 120°F. away from acids, ignition sources and oxidizing agents. Keep from freezing. Keep away from children and animals.

**DISPOSAL:** Dispose of container, residue, and excess product in accordance with all federal, state, and local laws and regulations.

**CONTAINER DESCRIPTION:** This product is available in quart, gallon, and 5-gallon containers.

## Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, N.C. 28079-5225 / 704-821-7643, 877-GO-4-GUNK

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.