

# PRODUCT INFORMATION



## WATER PUMP LUBE & ANTI-RUST

**CODE:** C1012

**PAGE:** 1 of 1

**DATE:** JAN 2008

**FUNCTION AND APPLICATION:** A water soluble oil lubricant with corrosion inhibitors compounded to lubricate and protect metals in automotive cooling systems. Can be used with Standard and Dex-Cool type anti-freeze.

**OUTSTANDING PROPERTIES:** Penetrates all working parts of the water pump. Helps to stop squeaking, chattering and squealing caused by dry seals. Constant lubrication prevents seals from deterioration. Keeps entire cooling system cleaner and free from dirt. Reduces foaming which increases heat transfer and inhibits evaporation of coolant.

**USE DIRECTIONS:** Pour entire contents of can into cooling system. Use after installing new or rebuilt water pump. If cooling system is dirty or rusted, clean system first.

**NOTE:** Used anti-freeze/coolant and radiator fluids may be considered hazardous in some areas. Dispose of in sanitary sewer system where permitted. Never pour onto ground or into storm or septic sewer systems. (See DISPOSAL, below) For extra capacity systems, use two cans of product.

**PRODUCT LIMITATIONS:** Will not seal existing leaks in cooling systems. Must be replenished if coolant is partially or totally lost.

**PRECAUTIONS:** Contains Naphthenic Petroleum Oil (64742-52-5), Triethanolamine (CAS# 102-71-6). Eye and Skin irritant. Harmful if swallowed. **FIRST AID:** If eye contacted, flush with water for at least 15 minutes while lifting eyelid and get prompt medical attention. If skin is contacted, wash thoroughly with soap and water. If irritation persists get prompt medical attention. If swallowed, do not induce vomiting. Call Poison Control Center, physician or Hospital Emergency Room Immediately.

**STORAGE & HANDLING:** Store in a cool place below 120°F away from acids, ignition sources and oxidizing agents. The wearing of contact lenses while working with this product is inadvisable. Keep out of reach of children and animals.

**DISPOSAL:** Use and dispose of product, container, residue and used Anti-freeze/coolant and Radiator Fluids in accordance with all local, state and federal laws and regulations. Where permitted, dispose of in sanitary sewer systems. Never pour onto ground or into storm sewer systems.

**CONTAINER DESCRIPTION:** Packaged 11 fluid ounce cone top plastic bottle.

## Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, N.C. 28079-5225 / 704-821-7643 / 877-GO-4-GUNK

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.