

# PRODUCT INFORMATION



## SUPER RADIATOR FLUSH

**CODE:** C2124

**PAGE:** 1 of 1

**DATE:** 03/28/2008

**FUNCTION AND APPLICATION:** Unclogs and cleans cooling systems easily and efficiently. Periodic cleaning of your automotive cooling system with SUPER RADIATOR FLUSH removes rust, heavy scale build ups, solder corrosion and residues common to malfunctioning cooling systems.

**OUTSTANDING PROPERTIES:** Works where other products fail. Contains only mild organic acids. Safe for use on aluminum as well as all other metals found in today's cooling systems. An economical way to flush your cooling system.

**USE DIRECTIONS:** To avoid injury, use extreme care when removing radiator cap when engine is hot. Do not add liquid to a hot radiator. 1) With engine warm and heater control on highest setting, drain system. **NOTE:** Used anti-freeze/coolant and radiator fluids may be considered hazardous in some areas. Dispose of in sanitary sewer system where permitted. Never pour onto ground or into storm or septic sewer systems. (See DISPOSAL, below) CAUTION: Do not siphon by mouth. Refill with water. 2) Start engine and flush system with hose until drain water runs clear. Stop engine. 3) Close drains. Add SOLDER SEAL® GUNK® SUPER RADIATOR FLUSH and fill with water. Replace radiator cap. 4) Restart engine and run at fast idle until it reaches normal operating temperature. Continue to run 15-20 minutes. 5) Repeat steps 1 and 2. Close drains. Refill with water and antifreeze solution as required. Replace radiator cap.

**PRODUCT LIMITATIONS:** KEEP AWAY FROM CHILDREN AND ANIMALS.

**PRECAUTIONS:** Contains Organic Acid (CAS# Confidential), Ethylene Diamine Tetra acetic Acid, Sodium Salt (CAS# 64-02-8), 2-Butoxy-ethanol (CAS# 111-76-2), Caustic Potash (CAS# 1310-58-3), Alkylbenzene Sulfonic Acid (CAS# 21176-87-0). Harmful or fatal if swallowed. Protect eyes. Avoid skin contact. **FIRST AID:** For eye contact, flush with water for at least 15 minutes while lifting eyelids and get prompt medical attention. For skin contact, wash thoroughly with soap and water. If irritation persists, get prompt medical attention. If swallowed, drink water with two teaspoons of bicarbonate of soda (baking soda). DO NOT INDUCE VOMITING. Call Poison Control Center, Physician, or Hospital Emergency Room Immediately. **WARNING:** This product contains a chemical known to the state of California to cause cancer and birth defects or other reproductive harm.

**STORAGE & HANDLING:** Store away from powdered metals.

**DISPOSAL:** Use and dispose of product, container, residue and used Anti-freeze/coolant and Radiator Fluids in accordance with all local, state and federal laws and regulations. Where permitted, dispose of in sanitary sewer systems. Never pour onto ground or into storm sewer systems.

**CONTAINER DESCRIPTION:** Packaged in 22 fluid ounce (1 pt, 6 oz) 650 ml plastic jug.

## Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, NC 28079-5225 / 704-821-7643, 877-GO-4-GUNK

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.